

CELESTIA SPARK

The Celestia Spark bollard offers understated elegance for urban environments.

Four height options ranging from 0.45m to 1.25m provide ideal illumination for walkways, cycleways, parks, and relaxation zones. Celestia Spark creates inviting and comfortable spaces by delivering a non-intrusive, pleasant light with a CRI exceeding 90. Its simple yet refined design seamlessly blends into various architectural styles.

Engineered for durability, the luminaire boasts IP65 and IK08 ratings, ensuring resistance to weather and impacts.



- Net Lumen Output (at Ta=25°C) 890 lm, 940 lm
- Power Consumption 12 W
- System Efficacy 74-78 lm/W
- Chromacity 3-step MacAdam
- Colour rendering index > 90
- Colour temperature 3000 K, 4000 K, on request 2200 K, 2700 K, RGBW
- Wiring FIX, on request dimmable
- Optical System Diffuser
- Materials Housing: Extruded aluminium
Diffuser: Extra clear polycarbonate
- Surface Finish Polyester powder paint
- Service Lifetime (Ta 40°C) 60,000 hours/L80/B15
- Dimmensions (L x W x H)
 - 045 ø 145 x 450 mm
 - 075 ø 145 x 750 mm
 - 100 ø 145 x 1000 mm
 - 125 ø 145 x 1250 mm

220-240V
50-60Hz

LED

CHROMATICITY
3
SDCM

CRI
90+
Ra

CCT
3000
K

CCT
4000
K

ECG

IP
65

IK
08