

STELARIS

Stelaris is the epitome of elegance and precision in urban lighting. Through a revolutionary approach to the side cut, Stelaris achieves a consistent aesthetic, creating a unified and sophisticated look.

Designed for optimal performance, the pole-mounted version excels in illuminating a variety of urban spaces. From bustling city streets and suburban roads to tranquil parks and pedestrian zones, delivers exceptional visibility and safety. Its special optics cater to both high and low traffic conditions, making it a versatile and effective lighting solution for any urban environment.



- Net Lumen Output (at Ta=25°C) 3362 lm
3210 lm
3362 lm
- Power Consumption 27 W
- System Efficacy 119-125 lm/W
- Chromacity 3-step MacAdam
- Colour rendering index > 80
- Colour temperature 3000 K, on request 2200 K, 2700 K, 4000 K, RGBW
- Wiring FIX, on request dimmable
- Optical System Lenses
- Beam Angle (C0-180, C90-270) parking 150° x 85°
pedestrian/cycle 125° x 45°
street 125° x 45°
- Materials Housing: Die-cast aluminium
Diffuser: Extra clear glass
- Surface Finish Polyester powder paint
- Service Lifetime (Ta 40°C) 60,000 hours/L80/B15
- Dimensions (L x W x H) 415 x 200 x 175 mm
- Opening for pole ø 60 mm

